

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
23 September 2004 (23.09.2004)

PCT

(10) International Publication Number  
**WO 2004/080918 A1**

(51) International Patent Classification<sup>7</sup>: **C04B 41/87**

(21) International Application Number:  
PCT/CZ2003/000019

(22) International Filing Date: 13 March 2003 (13.03.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **PROCHAZKA, Jan** [CZ/CZ]; 273 01 Kamené Zehrovice 23, Czech Republic (CZ).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MANUFACTURING OF PHOTOCATALYTIC, ANTIBACTERIAL, SELF-CLEANING AND OPTICALLY NON-INTERFERING SURFACES ON TILES AND GLAZED CERAMIC PRODUCTS

(57) Abstract: The principle of the deposition technique uses ultrafine crystals of ceramic oxides deposited relatively cold on melted or partially melted surfaces of ceramic tiles and other glazed ceramics, creating a spotty deposition without a significant change of optical properties of the surface. Because the desired nano-substance is deposited cold in a solid state form on the hot "sticky" surfaces and rapidly cooled down, deposited material is directly melted into the substrate surface, but its outer side remains unchanged. It allows creating a deposition with the desired parameters, for amplifying and extending the antibacterial protection in the dark, these surfaces may contain noble and heavy metals, deposited either dry as a part of the powder, or in a separate step, directly on the surface by wet deposition followed by drying and calcination.



**WO 2004/080918 A1**